



This long-link G60 chain is produced for the mooring companies certified NS9415, so that they can focus on the complexity of the mooring operations and can trust our long link chains to do their job.

No other chain maker has taken the same precautions in chain production; ensuring the minimization of the risk of hydrogen embrittlement. The chain pitch is specially designed for maximum flexibility and compatibility, allowing a secure vertical tensioning of the nets. These chains can also be used in the sinker tubes, where the weight is all that matters.

“NO PEELING” Hot Dip Galvanization: the zinc coating is performed according to ISO1461 with an average of 85µm zinc layer. It is metallurgically bonded with the chain base steel, through a delicate balance between the zinc bath temperature and dipping time, helping to prevent later chipping of the coating.

100% proof-loaded up to 62,5% of its G60 breaking force. Every single link is tested.



Product Number	Markings	Chain size metric Ø [mm]	Chain size imperial [inch]	Indicative BF breaking force [kg]	Indicative BF breaking force [lbs]	Weight [kg/mt]	Weight [lbs/ft]
95150	9 x 53 x 15	11/32" x 2.0866 x 0.5906	11.250	24,802	1,40	0.77
95288	...	11 x 64 x 18	7/16" x 2.5197 x 0.7087	13.000	28,660	2,10	1.16
94973	...	11 x 72 x 19	4/16" x 2.8346 x 0.7480	13.000	28,660	2,20	1.21
95077	...	13 x 80 x 22	1/2" x 3.1496 x 0.8661	16.300	35,935	2,90	1.60
95097	...	16 x 100 x 30	5/8" x 3.9370 x 1.1811	24.700	54,454	4,60	2.53
95101	...	19 x 110 x 35	3/4" x 4.3307 x 1.3780	32.100	70,768	6,50	3.58
95282	...	22 x 125 x 38	7/8" x 4.9 x 1.4961	46.600	102,735	8,70	4.79
95283	...	25 x 143 x 38	31/32" x 5.6 x 1.4961	60.000	132,277	10,30	5.68
95284	...	28 x 150 x 40	1 1/8" x 5.9055 x 1.5748	75.300	166,008	14,90	8.21
95285	...	30 x 159 x 42	1 3/16" x 6.29 x 1.6535	88.700	195,550	16,00	8.82
95286	...	32 x 170 x 44	1 1/4" x 6.6929 x 1.7323	98.300	216,714	19,00	10.47