



This fishing chain has the mechanical values of G95.

Made with a special alloy steel, it is quenched and tempered to G95 values to minimize the risk of hydrogen embrittlement.

It is specially designed for fishing trawlers, and it is not suitable for lifting applications.

100% proof loaded up to. Every link is single tested. Suitable for operating temperatures from -40 °C to +200 °C.

The chain is easy to assemble using connecting links or shackles. Its pitch is also designed to accommodate quick links and other fittings between 2 adjacent chain-links.

A full operating manual is provided, for a product manufactured in Europe using European made alloy steel.

The Breaking forces indicated below are indicative.



Vare nr. Item No.	Markings	Chain size metric Ø [mm]	Chain size imperial [inch]	BF breaking force [kg]	BF breaking force [lbs]	Weight [kg/mt]	Weight [lbs/ft]
75222	G9	10 x 40 x 15	3/8" x 1.5748 x 0.5906	15.000	33,069	1,98	1.09
75223	G9	13 x 52 x 19,5	1/2" x 2.0472 x 0.7677	25.000	55,116	3,35	1.85
75227	G9	16 x 64 x 24	5/8" x 2.5197 x 0.9449	38.000	83,776	5,13	2.83
75231	G9	19 x 76 x 29	3/4" x 2.9921 x 1.1417	54.000	119,049	7,20	3.97
On Request		22 x 86 x 26	7/8" x 3.3858 x 1.0236	70.000	154,323	9,90	5.46
On Request		26 x 92 x 31	1" x 3.6226 x 1.2205	95.000	209,439	13,66	7.53
75240		16 x 64 x 24	5/8" x 2.5197 x 0.9449	38.000	83,776	5,13	2.83
75241		19 x 76 x 29	3/4" x 2.9921 x 1.1417	54.000	119,049	7,20	3.97